



TYPE TS



Timken 3984 3920 Tapered roller bearing

Bearing No. 3984

Series	3900
Cone Part Number	3984
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹	54300 lbf
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) ²	14100 lbf
d	2.6250 in
B - Cone Width	1.1830 in
R - Cone Backface To Clear Radius ³	0.14 in
da - Cone Frontface Backing Diameter	2.91 in
db - Cone Backface Backing Diameter	3.15 in
Ab - Cage-Cone Frontface Clearance	0.08 in
Aa - Cage-Cone Backface Clearance	0.06 in
a - Effective Center Location ⁴	-0.18 in
C90 - Dynamic Radial Rating (90 million revolutions) ⁵	8090 lbf
C1 - Dynamic Radial Rating (1 million revolutions) ⁶	31200 lbf
C0 - Static Radial Rating	43000 lbf

3984 Bearing 2D drawings and 3D CAD models



Liaocheng City Hsn Bearing Co., Ltd.

C_{a90} - Dynamic Thrust Rating (90 million revolutions) ⁷	5570 lbf
K - Factor ⁸	1.45
G1 - Heat Generation Factor (Roller-Raceway)	75.2
G2 - Heat Generation Factor (Rib-Roller End)	21.3
Cg - Geometry Factor	0.109